

# 2K-FlexQuick- 2KFQ



## Application

For interior and exterior use. A white 2 Components epoxy based water-proof filler paste. Flexible making it very suitable for contracting and expanding woods, due to its unique properties also suitable for concrete repairs. The surface must be clean and dry. Pasta A (resin) and Pasta B (hardener) 1: 1 mixed together until homogeneous. More hardener does not cause faster curing but reduces water resistance and discolours the paint layer. Processing time (depending on the temperature) 20 minutes, after which it cures and it's adhesive power decreases.

## Special advantages

White! Odourless. Does not shrink and attaches to almost any surface (except for very smooth surfaces, for example, Teflon). Water resistant, flexible can handle unstable wood and temperature resistant to 80°C. Product properties to be treated as concrete or wood for sawing, sanding, nailing and screwing.

## Dilution

Ready for use, do not dilute. Appliances can be cleaned with Special T.

## Processing

Apply with filling knife. Do not process beneath 6°C and air humidity of > 80%.

## Drying time

At 20°C dry and repaintable within 3 hours. A higher temperature of 10-15°C cuts curing time in halve. temperature to low, curing is halted full cure can even take place after weeks, as the temperature rises. Protect product from moisture until full cure has taken place.

## Efficiency

Depending on the layer thickness, condition and suction of the substrate.

## Degree of gloss

Mat

## Colour

White

## Package

Set of 2 cartridges a 600 ml = 1 kg

## Binder

2 component epoxy

## Pigment

Titanium dioxide

## Specific gravity

Ca. 2 g/ml, 23°C

## Viscosity

Paste-like

## Flash point

Ca. 100°C

## Shelf life

1 year -Frost-free storage-

## VOS

105 g/ltr

## Conveyance

KCA



LAKFA Verffabriek BV  
Zeeburgerpad 116  
1019 AE AMSTERDAM

Tel.: +31-20-6947368  
Fax: +31-20-6650808  
info@lakfa.com | www.lakfa.nl