

PAINT STRIPPER ECO - ABME



Application

For removal of old oil, alkyd resin, dispersions, based on 2 components and acrylic paints. Can be applied on both vertical and horizontal surfaces. Apply thick on the substrate and allow to work for 10-20 minutes. In case of old thick paint layers, repeat treatment if necessary. If the paint is soaked loose, it can be removed with a filler knife and the surface can be washed with water.

Special advantages

Is easy to apply. Due to the low viscosity of the product, a thick layer can be applied in one go. Due to the strong stripping power, a lot of time is saved. Easy to wash off with water. Contains agents that prevent an applied layer to desiccate through evaporation, thereby achieving an optimal effect on the substrate. Contains no biocides, preservatives, methylene chloride, NMP, acids and lye. Doesn't effect metal, wood and stone substrates.

Important instruction

DO NOT process near fire or in direct sunlight. Workspace must be well ventilated. Clean equipment with water. Before use make a hole in the lid with a nail.

Processing

Apply with brush or filling knife. Do not process beneath 6°C and by an air humidity of > 80%.

Efficiency

ca. 500 g/m², dependent on condition and suction of the substrate.

Colour

Colourless

Package

Cartons of 2x5 ltr

Specific gravity

23°C, 0.987 g/ml

Viscosity

23°C, 2500 – 3300 mPa.s

Flash point

Ca. 0°C

Shelf life

1 year

VOS

900 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl