

# OUTDOOR DISPERSION - AD



## Application

For outside. An excellent weather resistant wall paint for concrete, masonry and plasterwork, chip board, hard- and insulating board, old good adhesion paints.

## Special advantages

ARTEKOCRYL AD is an odourless wall paint with excellent weather resistance. The covering power, adhesion and application is excellent. It gives an evenly distributed, mat surface.

## Dilution

Water, the product is ready for use. Clean Material with water.

## Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

Dust dry after 1 – 2 hours. After 4 – 6 hours repaintable, dependent on temperature and air humidity.

## Efficiency

Ca. 4 – 8 m<sup>2</sup>/kg, dependent on condition and suction of the substrate.

## Degree of gloss

Even mat

## Colour

White and tintable

## Package

Oval plastic pail of 20 kg

## Binder

Odourless plastic dispersion

## Pigment

Titanium dioxide and special extender

## Solid matter content

Ca. 60 - 65 weight %

## Specific gravity

Ca. 1.45 – 1.50 g/ml

## Viscosity

20°C, 1650 mPas

## Shelf life

1 year -Frost-free storage-

## VOS

2004/42IIA (c) (75/40) Max. 0 g/ltr

## Conveyance

KCA



LAKFA Verffabriek BV  
Zeeburgerpad 116  
1019 AE AMSTERDAM

Tel.: +31-20-6947368  
Fax: +31-20-6650808  
info@lakfa.com | www.lakfa.nl