

ARTEKO ROOF - ADG/S



Application

For exterior use. For the renewal of old roofs, gutters, asphalt, roofing felt, zinc, concrete or similar substrates. As a prime coat on tar and old roof felt, - ARTEKO ROOF - to prime dilute with 30% water. Concrete and plaster must be primed with ARTEKO ROOF PRIMER Nr.1, followed by 2 layers of ARTEKO ROOF undiluted (min. 2-2½ kg p / m²). Apply only in dry and warm weather and not below 6°C.

Special advantages

High elasticity also after several years. Easy to use. Solvent free so environmentally friendly. Weather-proof; The product has been used successfully for many years.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after 1 – 8 hours, dependent on temperature and air humidity.

Efficiency

Apply ± 2-2½ kg/m², dependent on condition and suction of the substrate.

Degree of gloss

Silky flat

Colour

Gray and Black.

Package

Plastic pail of 25 kg

Binder

Water-dispersed High Polymers

Pigment

Titanium dioxide and special fillers

Solid content

Ca. 72 – 74 wt. %

Specific gravity

Ca. 1.50-1.55 g/ml, 23°C

Viscosity

Pasty

Shelf life

1 year -Frost-free storage-

VOC

5 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl