

ARTEKO ELASTIC - AE



Application

For outside and inside. Watertight super elastic joint mastik sealer based on one-component. To caulk, fill, fix, glue and seal on wood, metal, glass, plasterwork as well as concrete, lime and cement surfaces, because ARTEKO ELASTIC is resistant against these alkaline influences.

Special advantages

Even after decades, the product retains its elasticity. Especially suited for calking of window frames, thresholds, porches and dilatation joints. Over-paintable with both waterborne and solvent based paints. Easy to apply, can be used without primer directly on clean surfaces.

Dilution

Ready for use, do not dilute. material can be cleaned with water.

Processing

Apply with filling knife or caulking gun. Do not process beneath 6°C and air humidity of > 80%.

Drying time

After 2-8 hours. dry matter, depending on temperature and humidity.

Efficiency

Depending on condition and absorpency of the substrate.

Degree of gloss

Matt to silk flat

Colour

White, gray, brown, green, semi-transparent, Sand.

Package

Carton à 24x320 ml = cartouchen,
Carton à 24x3kg = tins,
Carton à 4x5 kg

Binder

Water-dispersed High Polymers

Pigment

Titanium dioxide and special fillers

Solid content

Ca. 73 - 75 wt. %

Specific gravity

Ca. 1.44-1.46 g/ml, 23°C

Viscosity

Pasty

Shelf life

1 year -Frost-free storage-

VOC

5 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl