

FIXING PRIMER - AF/AFW



Application

For inside and outside. An universal environment friendly water borne fixing- and impregnation primer. Used as a primer sealer for concrete- and wall work (like ceilings with distemper or lime wash distemper and plaster) and especially to fix of strongly powdered and absorbing substrates. Apply AFW undiluted with a brush or roller evenly on the substrate. Dust dry after 1 hour and after 4 hours dry and repaintable, dependent of temperature and air humidity.

Special advantages

The ideal fix medium for ID, AD, CA and TEX. Environment friendly, practical odourless. Has an enormous penetration capacity in the substrate. Repaintable with water borne as well as solvent based paints.

Dilution

The product is ready for use. Clean Material with water.

Processing

Apply with a brush or roller. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after 1 hour. After 4 hours repaintable, dependent on temperature and air humidity.

Efficiency

Dependent on condition and suction of the substrate.

Colour

AF = Colourless (in jerry can milky white)
AFW = After drying transparent/white

Package

10 kg plastic jerrycans

Binder

Micro-disperse (hydrosol)

Pigment

AF = -, AFW = white pigment

Solid matter content

Ca. 13 - 17 weight %

Specific gravity

Ca. 1.00 - 1.05 g/ml

Viscosity

20°C, 60 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (h) (50/30) Max. 0 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl