

AQUA WOOD STAIN - AHL



Application

For interior and exterior. For wood substrates that require durable protection against all types of weather patterns. The product can be used on new substrates as primer, intermediate- and finishing coat.

Special advantages

Resistant against U.V.-rays and weather influences, good filling power, moisture control, does not blister, odourless and environmentally friendly.

Dilution

The product is ready for use.
Clean Material with water.

Processing

Apply with a special acrylic brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after 1 – 1½ hours. After 4 – 6 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 6 – 10 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Satin gloss

Colour

Pine, Teak, Nut, Oak, Ebony, and Colourless

Package

Cartons of 4x4 ltr.

Binder

100% Acrylic dispersion

Pigment

Micronized iron pigments

Solid matter content

Ca. 38 - 40 weight %

Specific gravity

Ca. 1.04 – 1.06 g/ml

Viscosity

23°C, 500 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (e) (150/130) Max. 55 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl