



AQUA LOCK - AL



Application

For exterior use, to durably protect walls, façades and other porous mineral substrates against driving rain and penetrating liquids. Contains solvent. Lets the substrate breathe after treatment. The look of the substrate changes hardly after treatment. Substrates have to be dry, degreased and dust free. Stir well before use, then apply 2 layers wet in wet. Protect parts that won't be treated against spatter, like glass and natural stone.

Special advantages

Ideal protection against the penetration of moist in walls and façades. Has a strong penetrating capacity and protects the substrate. Application with brush or airless.

Dilution

Ready for use, do not dilute. Clean appliances with white spirit.

Processing

Apply with brush or airless – Stir well before use. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After 1 hour dust dry, repaintable wet in wet.

Efficiency

Pro litre 4 m², strongly dependent on condition and absorption of the substrate.

Colour

Colourless

Package

20 ltr Metal drum

Binder

siloxane polymer

Solid matter content

Ca. 5 weight %

Specific gravity

Ca. 0.8 g/ml, 23°C

Viscosity

5 cP at 20°C.

Flash point

> 25°C

Shelf life

1 year cool storage

VOS

2004/42IIA (h) (750/750) Max. 750 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl