

ACRYLMULTIPRIMER - AMG



Application

For interior and exterior. For all wood sorts, particular suited for window-frames, window-sill, garden fences, old alkyd paint layers as well as various synthetic and metal materials. As ground layer for new wood, mid coat and renovation work. Dust dry ½-1½ hours, after 3-4 hours dry and repaintable, depending on temperature and humidity. Dilute with water.

Special advantages

100% acrylic based. Water dilutable. Easy to apply. High filling and cover power. Flow and adhesion are extremely good. Sandable. Repaintable with water based as well as alkyd paint. Moisture controlling.

Dilution

Water, the product is ready for use. Clean Material with water.

Processing

Apply with long haired brush, acryl roller and airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after ½ - 1½ hours. After 3 - 4 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 5 - 10 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Mat

Colour

White and tintable

Package

Cartons of 20 x 1 kg, and 4 x 5,5 kg

Binder

100% acrylic dispersion

Pigment

Titanium dioxide, special pigments and extender

Solid matter content

Ca. 57 - 59 weight %

Specific gravity

Ca. 1.35 - 1.40 g/ml

Viscosity

20°C, 1500 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (d) (150/130) Max. 77 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl