

AQUA MULTIVARNISH MAT - AMM



Application

For interior use. Transparent matt varnish for protecting parquet, wooden tables, stairs, chairs and walls, which are heavily laden. The substrate must be dry, dust and grease free. Multiple layers are required.

Special advantages

Resistant to high chemical and mechanical laden, alcohol resistant, high filling properties. Very good flow, excellent processing. Dries quickly, allowing multiple layers to be applied in one day. Water dilutable, environmentally friendly.

Dilution

Water max 3%, the product is ready for use. Clean Material with water.

Processing

Apply with brush and roller. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After ½ – 1½ hours dry. Dependent on temperature and air humidity.

Efficiency

Ca. 5 – 9 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Mat

Colour

Colourless

Package

1 ltr, 5 ltr, 10 ltr Jerrycans

Binder

Polyurethanecopolymer dispersion

Solid matter content

Ca. 32 - 34 weight %

Specific gravity

Ca. 1.00 – 1.05 g/ml

Viscosity

20°C, 370 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (e) (150/130) Max. 43 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl