

# MAT OIL - AO



## Application

For interior and exterior. In addition to chalet wood stain as well as wood stain top coat to make it better resistant and water-repelling, for fabrication of mat paints, as additive in classic oil paints, which improves the quality and makes it easier to process. **SHAKE WELL BEFORE USE !!!**

## Special advantages

This product exists since 1918 and is a must in every workplace. It has great resistance against the influence of UV-rays, has a pleasant and mild smell.

## Dilution

May NOT be diluted! Clean appliances with white spirit substitution.

## Processing

Apply with brush, roller and airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

Dust dry after 5 – 6 hours, complete trough drying after several days, dependent on temperature and air humidity.

## Efficiency

Ca 10 – 18 m<sup>2</sup>/kg, dependent on condition and absorption of the substrate.

## Degree of gloss

egg-shell gloss

## Colour

Colourless

## Package

Carton of 6x5 litres

## Binder

Special oil

## Solid matter content

Ca. 19 - 20 weight %

## Specific gravity

Ca. 0.82 - 0.84 g/ml, 23°C

## Viscosity

300 mPas, 20°C.

## Flash point

> 40°C

## Shelf life

Unlimited (after a long time the product improves)

## VOS

2004/42IIA (f) (700/700) Max. 487 g/ltr

## Conveyance

KCA

