

AQUA PARQUET COATING - APK



Application

For interior. For protection of parquet, wooden tables, -chairs, -walls, which are heavily mechanical and chemical laden. The substrate must be dry, dust- and fat free. After that man can apply several coats per day.

Special advantages

Resistant against heavily mechanical and chemical load, alcohol resistant, high filling power, easy to process. Quick drying, therefore several coats per day can be applied. Water dilutable, environment friendly.

Dilution

Water max 3%, the product is ready for use. Clean Material with water.

Processing

Apply with brush and roller. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After ½ – 1 hour dry. Dependent on temperature and air humidity.

Efficiency

Ca. 5 – 9 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Silk gloss.

Colour

Transparent

Package

1 ltr, 5 ltr, 10 ltr Jerrycans

Binder

Fine dispersed polyurethanecopolymer

Solid matter content

Ca. 30 - 32 weight %

Specific gravity

Ca. 1.00 – 1.05 g/ml

Viscosity

20°C, 370 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (e) (150/130) Max.
53,76 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl