

ANTI RUST - ARR/ARGG/ARF



Application

For outside. On galvanised tin-, iron- and copper rooftops also on gutters and tin package. If the substrate shows rust, then this must be removed beforehand. After that you can immediately paint with ANTI RUST. If the substrate has been painted previously, the paint has to be checked whether it still adheres. If this is the case you can -after removal of dirt - paint directly on it with ANTI RUST, if not then first remove the old paint layer.

Special advantages

Protects against rust. Keeps its elasticity for many years and is easy to apply.

Dilution

Is ready for use, evtl. with water. Material can be cleaned with water.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after 1 – 8 hours. Dependent on temperature and air humidity.

Efficiency

Ca. 0.8 – 1 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Silk gloss

Colour

Grey-green, roof-tile red, ferro-glimmer

Package

Oval plastic pail of 20 kg, Cartons of 4 x 5 kg

Binder

Elastic high-polymers mixed in water

Pigment

Titanium dioxide, anti-corrosion pigment

Solid matter content

Ca. 55 - 58 weight %

Specific gravity

Ca. 1.20 – 1.30 g/ml

Viscosity

Paste like at 23°C

Shelf life

1 year -Frost-free storage-

VOS

15 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl