

ACRYLIC SATIN GLOSS - AS



Application

For interior and exterior. For wood-work as doors, window-frames, wooden garden fences and walls. Prime with ACRYLMULTIGROUND - AMG or PRIMER - VL, RENOVATI-ONPRIMER - HVL, COMBI PRIMER - KVL, after that 2 layers of ACRYLIC SATIN GLOSS - AS. Dust dry after 1-1½ hours, repaintable after 3-4 hours, depending on temperature and air humidity. Dilute with water. Process with acryl brush or roller. DO NOT process beneath 6°.

Special advantages

No yellowing of the substrate. The paint layer stays snow-white and tackfree. Good flow, excellent cover power and edge coverage. Moisture control, odourless and environmental-ly friendly.

Dilution

Water, the product is ready for use. Clean Material with water.

Processing

Apply with acryl brush, roller and airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after 1 - 1½ hours. After 4 - 6 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 5 - 12 m²/kg, dependent on condi-tion and suction of the substrate.

Degree of gloss

Satin gloss

Colour

White and tintable

Package

Cartons of 4 x 5 kg

Binder

100% acrylic dispersion

Pigment

Titanium dioxide

Solid matter content

Ca. 52 - 54 weight %

Specific gravity

Ca. 1.25 - 1.28 g/ml

Viscosity

1450 mPas, 20°C

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (d) (150/130) Max. 74 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl