

AQUA TRANSPARENT SATIN MAT - ATS



Application

For interior. PU-dispersion based wear resistant clear satin mat varnish. Very suitable for finishing of doors, window frames, staircase steps, floors etc.

Special advantages

Excellent flow, durable even satin gloss. Good filling and supple handling. Fast drying.

Dilution

Water max 5%, the product is ready for use. Clean Material with water.

Processing

Apply with brush and roller. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after 1 - 2 hours, after 3 - 4 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 8 - 10 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Silk gloss.

Colour

Transparent

Package

1 ltr, 5 ltr, 10 ltr Jerrycans

Binder

Polyurethane copolymer

Solid matter content

Ca. 30 - 35 weight %

Specific gravity

Ca. 1.00 - 1.05 g/ml

Viscosity

710 mPas, 23°C

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (e) (150/130) Max. 42 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl