

# ACRYL WHITE ENAMEL - AWL



## Application

For interior and exterior. A high gloss, tack free paint. Can be used as topcoat for wood, pre-treated iron, zinc and aluminium. Also suitable for plasterwork, concrete and most synthetic substrates. First prime with our ACRYLMULTIGROUND - AMG or PRIMER - VL, after that 1-2 layers of ACRYL GLOSS ENAMEL - AWL.

## Special advantages

The layer doesn't stick, can trouble-free be used as window frame varnish. Has a good coverage and edge covering. Unequalled flow. Excellent absorbs vapour and keeps long it's gloss. High resistance against weather influences.

## Dilution

Water, the product is ready for use. Clean Material with water.

## Processing

Apply with long haired acrylic brush or roller. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

Dust dry after 1 - 1½ hours. After 4 - 6 hours repaintable, dependent on temperature and air humidity.

## Efficiency

Ca. 5 - 10 m<sup>2</sup>/kg, dependent on condition and suction of the substrate.

## Degree of gloss

High gloss

## Colour

White and tintable

## Package

Cartons of 4 x 5 kg

## Binder

100% acrylic dispersion

## Pigment

Titanium dioxide

## Solid matter content

Ca. 57 - 59 weight %

## Specific gravity

Ca. 1.35 - 1.40 g/ml

## Viscosity

1500 mPas, 20°C

## Shelf life

1 year -Frost-free storage-

## VOS

2004/42IIA (d) (150/130) Max. 80,3 g/ltr

## Conveyance

KCA



LAKFA Verffabriek BV  
Zeeburgerpad 116  
1019 AE AMSTERDAM

Tel.: +31-20-6947368  
Fax: +31-20-6650808  
info@lakfa.com | www.lakfa.nl