

CLEAN AIR - CA



Application

For interior. Super hiding paint. An universal double hiding interior paint, guaranteed emission and solvent free. This paint is developed after the latest state of technology. Especially suited for ceilings, walls, cement, etc. First pre-treat strongly absorbing substrates with FIXING PRIMER - AFW.

Special advantages

The paint is specially advised for hospitals, Retirement centre, School buildings, bedrooms, offices, bakery's, etc. Extremely high hiding power. Dries evenly mat. Excellent flow. Wash- and scrub resistant according to DIN 53778. No emission of harmful substances. Odourless. The painted rooms are very quickly ready for use again.

Dilution

Water max. 5%, the product is ready for use. Clean Material with water.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After 2 - 3 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 4 - 8 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Mat

Colour

White and tintable

Package

Oval plastic pail of 20 kg

Binder

Dispersed plasticizer without solvent

Pigment

Titanium dioxide and special filler

Solid matter content

Ca. 70 - 75 weight %

Specific gravity

Ca. 1.65 - 1.70 g/ml

Viscosity

20°C, 1650 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (a) (75/30) Max. 15 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl