

DECKENMATT SUPERIEUR - DMS



Application

For interior. For ceilings and walls. Low-tension and covers hair cracks. Isolates exceptionally (ex. nicotine, soot- and water stains). Especially for powdered and strongly absorbing substrates, like distemper and lime wash-distemper. Dilute with water or if necessary with **Special-thinner T** (Max. 3%). Processing with brush, roller or airless.

Special advantages

The product has an exceptionally covering power, has a **neutral odour**, is **low aromatic** and **environmentally friendly**. No spatter, no lapping defects. Dries white and evenly mat. Easy to use

Dilution

Ready for use, if necessary dilute with water or "Special-thinner T" (max. 3%). Clean appliances with water.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After ca. 1 – 2 hours dust dry. After ca. 24 hours completely dry, dependent on temperature and air humidity.

Efficiency

Ca. 3 – 8 m²/kg, dependent on condition and absorption of the substrate.

Degree of gloss

Mat

Colour

Snow White and tintable

Package

Oval plastic pail of 20 kg and Cartons of 4x6 kg

Binder

In water emulsified alkyd resin.

Pigment

Titanium dioxide and mineral filler

Solid matter content

Ca. 67 - 70 weight %

Specific gravity

Ca. 1.60 – 1.70 g/ml

Viscosity

20°C, 1500 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (a) (75/30) Max. 2 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl