

ECO MINERAL MAT - EMM



Application

For interior use, a ready to paint, high diffusion capable and good hiding power, silicate-based paint according to DIN 18363 for mineral substrates. Health and ecological friendly, fogging-active agent, solvent and plasticizer free. The alkalinity creates natural protection against fungal and mould growth. Suitable for any standard well bonded mineral substrate (plaster, concrete, brick-work), organic paint layers, plaster, plasterboard and glass-fibre. The substrate must be clean, dry and stable. Strong absorbing substrates must first be pre-treated with ECO MINERAL GROND - EMG.

Special advantages

Silified with the (mineral) substrate, does not blister, inseparable attachment. High diffusion capacity and moisture regulating. Due to the high PH value protects against fungal and/or micro-organisms. The material is free of solvent and plasticizer, health and ecological friendly. ECO MINERAL MAT - EMM has a mineral mat finish, Sidelight insensitive, available in light and dark colours.

Dilution

Water. Cleaning Material: Immediately after use with water and soap.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Within 4 - 5 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 4 - 5 kg/m², dependent on condition and suction of the substrate.

Degree of gloss

Evenly mat

Colour

White and tintable

Package

Oval plastic pail of 20 kg

Binder

Potassium water glass

Pigment

Titanium dioxide, filler and additives.

Solid matter content

Ca. 56 weight %

Specific gravity

Ca. 1.45 - 1.55 g/ml

Viscosity

20°C, ca. 11000mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (a) (75/30) Max. 1 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl