

GLOSSINOVA - GN



Application

For exterior and interior use. For demanding paint work on wood (e.g. window-frames, doors cupboards etc.), plasterwork and walls. First Apply our PRIMER, RENOVATION PRIMER, KOMBI-PRIMER or ACRYL-MULTIGROUND. Then apply GLOSSINOVA as mid coat or top coat. Dust free after 1 – 2 hours, repaintable after 4 – 5 hours. Application with brush, roller or airless, clean appliances with water.

Special advantages

High gloss finish with a fantastic flow and long open time. Easy to apply, the drying, adhesion and edge coverage are exceptional. Scratch- and wear resistant. The product has a high hiding power.

Dilution

The product is ready for use. Clean Material with water.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after 1 – 2 hours. After 4 – 5 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 8 – 12 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Highgloss

Colour

White and tintable

Package

Cartons of 20 x 1 kg, and 4 x 5 kg

Binder

Aqueous urethane-alkyd resin

Pigment

Titanium dioxide and special pigments

Solid matter content

Ca. 50 - 55 weight %

Specific gravity

Ca. 1.20 – 1.25 g/ml

Viscosity

20°C, 1200 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (d) (150/130) Max. 1 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl