

HI-TECX - HT



Application

For interior use. Super hiding power. Plasticizer and solvent free. This paint is developed after the latest state of technology, wet wear class 3 according to EN 13300. Exceptionally suited for project wallpaper, ceilings, walls, cement, plaster, plasterboard, good bonded old paint coatings, hardboard, glass fibre, brickwork etc. Strong absorbing substrates pre-treat first with Fix primer - AFW.

Special advantages

This paint is specially recommended for hospitals, elderly homes, school buildings, bedrooms, offices, bakeries, etc. Extremely high hiding power. Dries up evenly mat. Excellent flow. Wet wear resistance class 3 according to EN 13300. No emissions of harmful substances. Odourless. The painted areas can very fast be occupied again.

Dilution

No dilution, the product is ready for use. Cleaning Material: Immediately after use with water and soap.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Within 4 - 5 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 5 - 8 kg/m², dependent on condition and suction of the substrate.

Degree of gloss

Mat

Colour

White and tintable

Package

Oval plastic pail of 20 kg

Binder

Vinyl acetate-Ethylene

Pigment

Titanium dioxide.

Solid matter content

Ca. 60 - 65 weight %

Specific gravity

Ca. 1.60 - 1.65 g/ml

Viscosity

18 - 19 poise, 23°C

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (a) (75/30) Max. 1 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl