

ADHESION PRIMER - HVL



Application

For interior and exterior. Excellent adhesion on most substrates with a minimal pre-treatment. As a renovation layer on old paint layers and wood as well as on diverse synthetics and metals (adhesion test is recommended). Special for interior but also for exterior. Within 1-2 hours dust dry, after 4-6 hours repaintable. Dilution up to 5% with white spirit. Process with brush, roller or airless-spray.

Special advantages

Good filling and hiding power, good edge coverage and flow, easy to use, quick and good sand able. This product is developed for quick renovation work.

Dilution

Ready for use, if needed with Special T up to max. 5%. Appliances can be cleaned with Special T.

Processing

Apply with brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Within 1-2 hours dust dry. After 4-6 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 6 - 10 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Matt

Colour

White and tintable

Package

Cartons of 4x5 kg and cartons of 20x1 kg

Binder

Alkyd resins combination

Pigment

Titanium dioxide and special filler.

Solid matter content

Ca. 73 - 76 weight %

Specific gravity

Ca. 1.40 - 1.45 g/ml, 23°C

Viscosity

Ca. 1010 mPas, 23°C

Flash point

Ca. 40°C

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (i) (600/500) Max. 359 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl