

KOMBI SATIN - KS



Application

For interior and exterior. A water based satin gloss enamel and emulsified in an oil alkyd resin. Dilutable with water, Dust dry after 1½ - 2 hours, repaintable after 24 hours. Application with brush, roller and airless-spray. Stir well before use.

Special advantages

Easy to apply, with an evenly flow, excellent edge coverage, good hiding power and adhesion. Barely yellowing. Scratch- and wear resistant. Guaranteed solvent free. No environment harmful gas emission, odourless.

Dilution

Water, the product is ready for use. Clean Material with water.

Processing

Apply with brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Dust dry after 1½ - 2 hours, after 24 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 6 - 8 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Satin gloss

Colour

White and tintable

Package

Cartons of 4 x 5 kg

Binder

Emulsified linseed oil alkyd resin

Pigment

Titanium dioxide and special pigments

Solid matter content

Ca. 50 - 55 weight %

Specific gravity

Ca. 1.25 - 1.30 g/ml

Viscosity

1450 mPas, 20°C

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (d) (150/130) Max. 74 g/ltr

Conveyance

KCA



LAGER LAKFA BV c/o Ziegler (Schweiz) AG
Signalstrasse 101 | CH-4058 Basel
Tel.: 061-6912160 | Fax: 061-6958458
info@lakfa.com | www.lakfa.ch

LAKFA Verffabriek BV
Zeeburgerpad 116 | NL-1019 AE AMSTERDAMI
Tel.: +31-20-6947368 | Fax: +31-20-6650808
info@lakfa.com | www.lakfa.com