

# KOMBI PRIMER - KVL



## Application

For interior and exterior. A water based primer, emulsified in an oil alkyd resin. For new wood as for old well adhering paint layers. Dilutable with water, Dust dry after 2 - 3 hours, re-paintable after 24 hours. Application with brush, roller and airless-spray. Stir well before use.

## Special advantages

Good hiding power and flow, Very good adhesion and penetrating capacity in new wood substrates. Good sand able, moisture controlling, odourless, easy to process

## Dilution

Water up to 4 - 5%, the product is ready for use. Clean Material with water.

## Processing

Apply with brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

Dust dry after 2 - 3 hours, after 24 hours repaintable, dependent on temperature and air humidity.

## Efficiency

Ca. 8 - 10 m<sup>2</sup>/kg, dependent on condition and suction of the substrate.

## Degree of gloss

Mat

## Colour

White and tintable

## Package

Cartons of 20x1 kg and 4 x 5,5 kg

## Binder

Emulsified linseed oil alkyd resin

## Pigment

Titanium dioxide and special pigments

## Solid matter content

Ca. 57 - 59 weight %

## Specific gravity

Ca. 1.35 - 1.40 g/ml

## Viscosity

20°C, 1500 mPas

## Shelf life

1 year -Frost-free storage-

## VOS

2004/42IIA (d) (150/130) Max. 77 g/ltr

## Conveyance

KCA



LAKFA Verffabriek BV  
Zeeburgerpad 116  
1019 AE AMSTERDAM

Tel.: +31-20-6947368  
Fax: +31-20-6650808  
info@lakfa.com | www.lakfa.nl