

# KOMBI ENAMEL - KWL



## Application

For interior and exterior. A water based high gloss enamel and emulsified in an oil alkyd resin. For high quality paint work on wood, windows, walls etc. Dust dry after 1½ - 2 hours, repaintable after 24 hours. Application with brush, roller and airless-spray. Stir well before use.

## Special advantages

Long open time, good flow. Excellent edge coverage, hiding power and adhesion. Odourless.

## Dilution

Water, the product is ready for use. Clean Material with water.

## Processing

Apply with brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

Dust dry after 1½ - 2 hours, after 24 hours repaintable, dependent on temperature and air humidity.

## Efficiency

Ca. 7 - 8 m<sup>2</sup>/kg, dependent on condition and suction of the substrate.

## Degree of gloss

High gloss

## Colour

White and tintable

## Package

Cartons of 4 x 5 kg

## Binder

Emulsified linseed oil alkyd resin

## Pigment

Titanium dioxide

## Solid matter content

Ca. 50 - 55 weight %

## Specific gravity

Ca. 1.25 - 1.30 g/ml

## Viscosity

1450 mPas, 20°C

## Shelf life

1 year -Frost-free storage-

## VOS

2004/42IIA (d) (150/130) Max. 80,3 g/ltr

## Conveyance

KCA



LAKFA Verffabriek BV  
Zeeburgerpad 116  
1019 AE AMSTERDAM

Tel.: +31-20-6947368  
Fax: +31-20-6650808  
info@lakfa.com | www.lakfa.nl