

# ROLL EASY SPACHTEL - RES



## Application

For interior use. Ready for use paste, can be applied with a roller. For evening/reducing of unevenness in walls and ceilings, as a preparation for painting or wallpaper work. Can be applied on any well bonded standard mineral substrate (plaster, concrete, brickwork), lime stone panels, plasterboard, hardboard, finished parts and old paint layers. Very easy to apply, the product can be applied with a roller, filling knife / trowel and airless spray. Solvent and plasticizer free. The substrate must be clean, dry, grease free and stable. Pre-treat strong absorbing, powdery, sanding or gritting surfaces with a primer from the Lakfa product range.

## Special advantages

Easy to apply with roller! Layer thickness 0 to 4 millimetres in one go. Minimum chance of blistering due to very good filling capacity. The material is solvent and plasticizer free. Dries up evenly white.

## Dilution

Ready for use. Cleaning Material: Immediately after use with water.

## Processing

Apply with a roller, filling knife / trowel or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

Dependent on layer thickness, temperature and air humidity.

## Efficiency

Dependent on layer thickness, condition and absorption of the substrate.

## Degree of gloss

Mat

## Colour

White

## Package

Oval plastic pail of 10 and 20 kg

## Binder

Plastic dispersion

## Pigment

Light fillers and additives.

## Solid matter content

Ca. 60 - 65 weight %

## Specific gravity

Ca. 1.30 - 1.35 g/ml

## Viscosity

200000 - 250000 mPas

## Shelf life

1 year -Frost-free storage-

## VOS

2004/42IIA (a) (75/30) Max. <0,1 g/ltr

## Conveyance

KCA



LAKFA Verffabriek BV  
Zeeburgerpad 116  
1019 AE AMSTERDAM

Tel.: +31-20-6947368  
Fax: +31-20-6650808  
info@lakfa.com | www.lakfa.nl