

SATIN SATIN GLOSS ENAMEL - S



Application

For interior and exterior use. For high quality painting on wood (e.g. window frames, windows, doors, cupboard etc), stucco and walls. To ground first use our, PRECOAT ENAMEL, ADHESION PRECOAT ENAMEL, ACRYLMULTIGROUND. Then SATIN as mid or topcoat. Dustfree dry after 1 - 2 hours, tack-free after 3 - 4 hours and repaintable after 16 hours. Workable with brush, roller or airless, if necessary dilute with White Spirit or a low aromatic dilution.

Special advantages

Almost non-yellowing, scratch and abrasion resistant. Easy to process, even flow out. The product has a high covering power.

Dilution

Ready for use, if necessary dilute with White Spirit (Sangajol) or universal diluents.

Processing

Apply with brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

Within 1-2 hours dust dry. After 3-4 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 8 - 12 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Satin gloss

Colour

White and tintable

Package

Cartons of 4x5 kg, 6x3 kg and 20x1 kg

Binder

A combi-resin on sunflower oil basis.

Pigment

Titanium dioxide and specialpigments

Solid matter content

Ca. 73 - 76 weight %

Specific gravity

Ca. 1.30 - 1.35 g/ml, 23°C

Viscosity

Ca. 1010 mPas, 23°C

Flash point

Ca. 36°C

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (i) (600/500) Max. 313 g/ltr

Conveyance

KCA

