

SATIN GLOSS WALL PAINT - SD



Application

For interior use. A high-quality super hiding wall paint based on a 100% acrylic dispersion. Can be used on wind dry cement - f.e. concrete-substrates and ceilings. For strongly absorbing substrates first apply a prime coat with FIXING PRIMER - AFW.

Special advantages

Extremely high hiding power, the first layer is directly bright white with an evenly mat and level surface.

Dilution

Water (max 5%). Clean Material with water.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After 1 - 6 hours dust dry. After 6 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 6 - 10 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Satin gloss

Colour

White and tintable

Package

Oval plastic pail of 18 kg

Binder

Vinyl acetate polymer

Pigment

Titanium dioxide and special filler

Solid matter content

Ca. 50 - 55 weight %

Specific gravity

Ca. 1.25 - 1.30 g/ml

Viscosity

20°C, 1500 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (b) (150/100) Max. 3 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl