

# SATINOVA - SN



## Application

For exterior and interior use. For demanding paint work on wood (e.g. window-frames, doors cupboards etc.), plasterwork and walls. First Apply our PRIMER, RENOVATION PRIMER, KOMBI-PRIMER or ACRYL-MULTIGROUND. Then apply GLOSSINOVA as mid coat or top coat. Dust free after 1 – 2 hours, repaintable after 4 – 5 hours. Application with brush, roller or airless, clean appliances with water.

## Special advantages

Satin gloss finish with a fantastic flow and long open time. Easy to apply, the drying, adhesion and edge coverage are exceptional. Scratch- and wear resistant. The product has a high hiding power.

## Dilution

The product is ready for use. Clean Material with water.

## Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

Dust dry after 1 – 2 hours. After 4 – 5 hours repaintable, dependent on temperature and air humidity.

## Efficiency

Ca. 7 – 10 m<sup>2</sup>/kg, dependent on condition and suction of the substrate.

## Degree of gloss

Satin gloss

## Colour

White and tintable

## Package

Cartons of 20 x 1 kg, and 4 x 5 kg

## Binder

Aqueous urethane-alkyd resin

## Pigment

Titanium dioxide and special pigments

## Solid matter content

Ca. 50 - 55 weight %

## Specific gravity

Ca. 1.20 – 1.25 g/ml

## Viscosity

20°C, 1200 mPas

## Shelf life

1 year -Frost-free storage-

## VOS

2004/42IIA (d) (150/130) Max. 1 g/ltr

## Conveyance

KCA



LAKFA-Verfabriek BV (LAKFA-Verfabriek (Schweiz) AG)  
Zeeburgerpad 11068 Basel  
1019 AE AMSTERDAM  
Tel: +31 20 669 47368 Fax: +31 20 669 0808  
info@lakfa.com | www.lakfa.ch

LAKFA-Verfabriek BV  
Zeeburgerpad 11068 AMSTERDAM  
Tel: +31 20 669 47368 Fax: +31 20 669 0808  
info@lakfa.com | www.lakfa.nl