

S.O.S.



Application

For interior and exterior. For painting of moist exterior walls, ceilings and basement walls, the solution against damp-stains, mould and moss. Clean powdered substrate first with a wire brush. Let water leakage dry and if necessary fill any unevenness with special cement. Apply first layer with a half hard brush or hard block brush, so that the pores of the substrate are well filled. Always fully saturate unpainted substrates with SOS. After 25 hours apply second layer with brush or roller. **WARNING:** Ventilate well during painting.

Special advantages

SOS is the ideal product to embellish substrates with damp-stains, mould and moss. For old and new substrates with moisture problems. Has an exceptionally adhesion quality on moist substrates. Excellent hiding power, two layers are mostly sufficient.

Dilution

Ready for use, if necessary dilute with Special T. Appliances can be cleaned with Special T.

Processing

Apply with brush or roller. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After ca. 23 – 25 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 1 – 2½ m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Matt

Colour

White (can only be coloured in light colours)

Package

Pails of 18,5 kg

Binder

Special acryl polymer.

Pigment

Titanium dioxide and fillers

Solid matter content

Ca. 60 - 65 weight %

Specific gravity

Ca. 1.24 - 1.28 g/ml, 23°C

Viscosity

Ca. 40-45 poise, 20°C

Flash point

>39°C

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (i) (600/500) Max. 500 g/l

Conveyance

KCA

