

# SPEED FILLER - SP



## Application

For interior and exterior. An quick drying high filling , elastic knifing filler. For primed wood and steel substrates, as for well sanded and degreased alkyd resin substrates and polyester.

## Special advantages

SP distinguishes it self by it's excellent filling capacity, elasticity and supple application. Is already sand able and repaint able after 4 - 5 hours, without a mid coat.

## Dilution

Ready for use. Appliances can be cleaned with white spirit.

## Processing

Apply with filling knife. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

Sand able in direct repaint able after 4 - 5 hours, dependent on temperature and air humidity.

## Efficiency

Ca. 8 - 12 m<sup>2</sup>/kg. Dependable of the layer thickness and on condition and suction of the substrate.

## Degree of gloss

Mat

## Colour

Off-white

## Package

Cartons of 36 tubes à 320 gr and cartons of 8 x 2 kg

## Binder

Alkyd resin

## Pigment

Titanium dioxide and filler

## Solid matter content

Ca. 83 - 85 weight %

## Specific gravity

Ca. 1.75 - 1.80 g/ml, 23°C

## Viscosity

Paste-like

## Flash point

Ca. 25°C

## Shelf life

1 year -Frost-free storage-

## VOS

269 g/ltr

## Conveyance

KCA



LAKFA Verffabriek BV  
Zeeburgerpad 116  
1019 AE AMSTERDAM

Tel.: +31-20-6947368  
Fax: +31-20-6650808  
info@lakfa.com | www.lakfa.nl