



# SURFACE SHIELD - SS



## Application

For outside and inside. To protect; 1 component water and solvent based systems and of wood such as table, chairs, walls and flooring, which are mechanically and chemically exposed. The substrate must be dry, dust- and grease free. After which one can apply several layers in a day.

## Colour

White.  
SSM can be tinted in all colours.  
SSS and SSH can only be tinted in light colours

## Package

Oval plastic pail of 13 ltr

## Binder

Aqueous polyester polyurethane

## Solid matter content

Ca. 38 - 42 weight %

## Specific gravity

Ca. 1.05 - 1.10 g/ml

## Viscosity

20°C, 400 mPas

## Shelf life

1 year -Frost-free storage-

## VOS

2004/42IIA (e) (150/130) Max. 2,4 g/ltr

## Conveyance

KCA



## Special advantages

Non-yellowing. Withstands mechanical and chemical exposure, alcohol-resistant, high filling power, easy to apply. Dries quickly allowing application of multiple layers in a day. Water-dilutable, environmentally friendly and odourless.

## Dilution

Water max 3%, the product is ready for use. Clean Material with water.

## Processing

Apply with brush, roller or airless. Do not process beneath 6°C and by an air humidity of > 80%.

## Drying time

After ½ - 1 hours dry. Dependent on temperature and air humidity.

## Efficiency

Ca. 8 - 12 m2/kg, dependent on condition and suction of the substrate.

## Degree of gloss

SS-M = Matt  
SS-S = Satin  
SS-H = High gloss.



LAKFA Verffabriek BV  
Zeeburgerpad 116  
1019 AE AMSTERDAM

Tel.: +31-20-6947368  
Fax: +31-20-6650808  
info@lakfa.com | www.lakfa.nl