

TEX EXTRA WALL PAINT - TEX



Application

For interior and exterior use. A durable latex wall paint for wind dry cement, concrete, stone, wood, wall-paper and pressed plates. If you want to deliver a completely lap free and evenly mat paint work, in this you're product, there is no better!!! Pre-treat absorbing substrates first with FIXING PRIMER - AFW. Then Apply 1 - 2 layers TEX extra wall paint.

Special advantages

The hiding power is excellent, the paint doesn't saponify, quick drying, hard but elastic.

Dilution

Water, the product is ready for use. Clean Material with water.

Processing

Apply with a brush, roller or airless-spray. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After 1 - 2 hours dust dry. After 4 - 6 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 4 - 8 m²/kg, dependent on condition and suction of the substrate.

Degree of gloss

Mat

Colour

White and tintable

Package

Oval plastic pail of 20 kg

Binder

Plastic dispersion based on polyvinyl acetate

Pigment

Titanium dioxide and special filler

Solid matter content

Ca. 70 - 75 weight %

Specific gravity

Ca. 1.60 - 1.65 g/ml

Viscosity

20°C, 1400 mPas

Shelf life

1 year -Frost-free storage-

VOS

2004/42IIA (a) (75/30) Max. 24 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl