

WOODGEL - WG



Application

For exterior use. For painting of wood substrates, which must be protected against strong weather influences, can be used as ground-, intermediate- and topcoat. Exterior use: 2-3 layers, window frames 3-4 layers. WOODGEL colourless can be used as a primer to provide the best possible U.V. protection. Do not apply when the humidity is >15%.

Special advantages

Spatter free, very easy to apply. No blistering of the paint layer, good filling power. Very resistant to U.V. rays.

Dilution

Ready for use, do not dilute.

Processing

In dipping bath or apply with brush or roller. Do not process beneath 6°C and by an air humidity of > 80%.

Drying time

After 12 hours repaintable, dependent on temperature and air humidity.

Efficiency

Ca. 80 – 100 ml/m², smooth wooden surface. 200 – 250 ml/m², rough sawn wood substrates, dependent on condition and suction of the substrate.

Degree of gloss

Matt

Colour

1. Pine 2. Teak 3. Nut
4. Oak 5. Ebony 6. Colourless

Package

Cartons of 4x5 ltr

Binder

Alkyd resins base

Pigment

Iron oxide.

Solid matter content

Ca. 17 - 20 weight %

Specific gravity

Ca. 0.80 - 0.85 g/ml, 23°C

Viscosity

kinematic >8 mm²/s, 40°C,
ISO 3104/3105.

Flash point

Ca. 55,5°C

Shelf life

1 year

VOS

2004/42IIA (f) (700/700) Max. 700 g/ltr

Conveyance

KCA



LAKFA Verffabriek BV
Zeeburgerpad 116
1019 AE AMSTERDAM

Tel.: +31-20-6947368
Fax: +31-20-6650808
info@lakfa.com | www.lakfa.nl